












广州赛奥碳纤维
ATA CFT Guangzhou Co., Ltd.
www.atamachinery.com

广州赛奥卷绕机产品总览 Overview of ATA Winders

系列 Series	1、特种纤维 Specialty Fiber				2、扁丝 Flat Yarn	
型号 Model	AW10	AW10DS	AW11	AW10F	AW20 (ATA600D)	AW22 (ATA600)
图片 Picture						
应用领域 Applications	1.1.高性能：芳纶、超高分子、PBO纤维、聚酰亚胺PI、玄武岩纤维 High performance fiber: Aramid fiber, UHMWPE, PBO, PI, Basalt fiber 1.2.特种有机纤维：PEI纤维；特氟龙纤维；PVDC纤维；PEEK纤维；PPS纤维 Specialty organic fiber: PEI, Teflon, PVDC, Peek PPS 1.3.特种无机纤维：氧化铝纤维；石英纤维；Specialty inorganic fiber: Alumina fiber, Quartz fiber 1.4.纤维后处理：浸胶丝；PVC涂层丝；并股丝；玻纤倒筒 After-treatment : Coated yarn, PVC coated yarn, Paralled yarn, Glass rewinding				编织袋、吨袋、篷布、地毯基布、人工草丝、纤化绳 Woven bag, Ton bag, Tarpaulin, Base fabric for carpet, Artificial grass, Chemical fiber rope	
工作速度 Winding Speed (m/min)	200-450	50-150	200-450	150-350	200-450	200-450
纱管规格 Tube Size (mm)	∅ 94X250 ∅ 94X290	∅ 94X250 ∅ 94X290	∅ 94X250 ∅ 94X290	∅ 94X250 ∅ 94X290	∅ 94X290	∅ 94X290
最大直径 Max. Diameter (mm)	280	280	250	280	280	250
系列 Series	3、碳丝+原丝 Carbon fiber + Precursor					
型号 Model	AW30PX	AW30R	AW33	AW33H	AW35 (AW60L)	AW36 (AW60H)
图片 Picture						
应用领域 Applications	碳纤维束预浸带 Carbon fiber towpreg	沥青基碳丝、氧化铝纤维 Pitch-based carbon fiber、Alumina fiber	碳丝分丝倒筒，PAN基碳丝 Carbon fiber separation and rewinding , PAN carbon fiber		PAN基原丝 PAN precursor	
工作速度 Winding Speed (m/min)	20-100 (3-24)K	5-50	3-15 (1-24)K	3-15 (48-60)K	50-150 (12-24)K	50-150 (12-24)K
纱管规格 Tube Size (mm)	∅ 76X280	∅ 76.X280	∅ 76.2X280	∅ 76.2X280	∅ 133x550	∅ 133x800
最大直径 Max. Diameter (mm)	250	200	250	330	600	800
系列 Series	4、无往复卷绕 Non-traverse winding			5、单丝 Monofilament		6、平行 Parallel
型号 Model	AW40 (AW90)	AW40P (AW90P)	AW40PR (AW90PR)	AW50 (AW70)	AW55 (AW77)	AW60 (AW70N)
图片 Picture						
应用领域 Applications	丝束预浸带、分切带、沥青基碳纤维原丝、碳化硅SIC、带衬纸(膜)丝、玄武岩纤维 Towpreg, Silt tape, Pitch-based Carbon Fiber, Silicon Carbide (SIC), Tow with film, Basalt fiber			PA单丝、PET单丝、假发单丝、运动鞋面单丝 Monofilament of PA, PET, Wig, Sport shoes		魔术贴、金拉线、云母带、无纺布带、柔性导线、轮胎冠带层、安全线 Velcro, Gold wire, Mica tape, Non-woven fabric tape, Flexible conductors, Tyre cap ply, Safety line
工作速度 Winding speed (m/min)	10-40	50-150 (带宽Tape 5-30mm)	50-150 (带宽Tape 5-30mm)	100-300	100-300	100-200
纱管规格 Tube Size (mm)	∅ 152X280	∅ 76.2X280 ∅ 29.8X280	∅ 76.2X280 ∅ 29.8X280	20X315X250	20X315X250	∅ 76.2X280 ∅ 29.8X280
最大直径 Max. Diameter (mm)	250	250	250	250	250	250